


USE MIL-H-5606 HYDRAULIC FLUID

REV A Change #1 to Hex Head from SHCS 10-22-08 GRH
Add #19 to Nordloc from AN Washer



1	BOLT (Torq 100 in-lb)	.25-20X1.50HH	3
2	WASHER	AN960-416L	2
3	SHCS	AN4-17A	2
4	STATIONARY BRK SHOE, 4"/UL	SBS1	1
5	LINING, 4" ULTRALIGHT	M66-102	2
6	BRASS RIVET	4-6	2
7	SPACER, 4"/ULTRALIGHT BRAKE	BSP40	5
8	BRAKE PLATE	BPA.75MH or BPA.62MH	1
9	BRASS RIVET	4-4	2
10	MOVEABLE BRK SHOE, 4"/UL	MBS1	1
11	PISTON, 4" BRAKE	PI-2D	2
12	O-RING BUNA N	2-210	2
13	PUCK HOUSING, 4" BRAKE	PH-3	1
14	DUST PLUG	.234-.50IL	1
15	BRAKE BLEEDER VALVE	F6446-007	1
16	BRAKE BLEEDER SEAT	BBS-16	1
17	LOCK NUT	.25-28NYLOC	2
18	CAPLUG	1X	1
19	WASHER	NL1/4	3

NO. PART NAME INVENTORY NO. REQ'D

3-4PH3BRAKE MATCO mfg
2361 S 1560 West
WOODS CROSS, UT 84087 (801) 335-0582

DUAL PISTON FOUR INCH BRAKE ASSEMBLY

DRAWN BY: GARY P. LANGFORD
AUTHORIZED BY:

SCALE: NONE
DATE: JAN. 30, 1991

REVISION
A